CGL CC48 - KI_x

DESCRIPTION:

CGL CC KIx 48- is a coconut shell activated carbon specifically developed for the nuclear industry. Available with KIx, amines or co-impregnated KIx/amines for entrapment of radioactive organo-iodine species from the air.

Physical Properties

ACTIVITY for CCL ₄ , (ASTM D3467-94)	60, minimum
BULK DENSITY, AVERAGE	34 lbs / cu ft
HARDNESS, (ASTM D3808-79)	98, min
MOISTURE, AS PACKED, (ASTM D2867-95)	2 %
KI CONTENT	5 %
ASH CONTENT, TYPICAL	2 %

This information has been gathered from standard reference materials and/or test procedures and is believed to be true and accurate. It is offered solely for your consideration and verification. None of the information presented shall be construed as constituting a warranty or representation, expressed, write, or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes, or that its use does not conflict with existing patent rights. No license is granted to infringe on any patent rights or practice any patent inversion.

2335 NW 29TH AVENUE, PORTLAND, OR 97210 PHONE: (800) 777-4044 FAX: (503) 225-0137

WWW.CAMERONGREATLAKES.COM EMAIL: SALES@CGLCARBON.COM