



CAMERON GREAT LAKES, INC.

MOLECULAR FILTRATION SPECIALISTS

CGL CP48 -SU

DESCRIPTION:

CP 48-SU is a sulfurized bituminous coal based pelletized activated carbon of high adsorptive capacity . It is specifically designed for the capture of mercury vapors.

APPLICATIONS:

It is ideally suited for critical applications such as destruction of fluorescent light bulbs, and other mercury containing devices.

Physical Properties

ACTIVITY for CCL ₄ , (ASTM D3467-94) (BASE MATERIAL)	60, minimum
BULK DENSITY, TYPICAL	35 lbs. cu ft
HARDNESS, (ASTM D3808-79)	98, minimum
MOISTURE, AS PACKED, (ASTM D2867-95)	2 %
ASH CONTENT, TYPICAL	10 - 12 %
SULFUR CONTENT, % BY WEIGHT	10 %, minimum

This information has been gathered from standard reference materials and/or test procedures and is believed to be true and accurate. It is offered solely for your consideration and verification. None of the information presented shall be construed as constituting a warranty or representation, expressed, write, or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes, or that its use does not conflict with existing patent rights. No license is granted to infringe on any patent rights or practice any patent inversion.

2335 NW 29TH AVENUE, PORTLAND, OR 97210
PHONE: (800) 777-4044 FAX: (503) 225-0137

WWW.CAMERONGREATLAKES.COM
EMAIL: SALES@CGLCARBON.COM